

# MATERIAL SAFETY DATA SHEET

MC-X-01046

MSDS NUMBER

DPM 222

## PRODUCT IDENTIFICATION

TRADE NAME Compressed Rubber/Asbestos Sheet Packing			GENERIC NAME Gasketing material		
MANUFACTURER'S NAME Manville Building Materials Corporation			CAS NUMBER		
ADDRESS (STREET) P. O. Box 5108			PHONE NUMBER (303) 978-3120		
CITY Denver	STATE Colorado	ZIP 80217	CHEMICAL STRUCTURE		

## I • PRODUCT INGREDIENTS

MATERIAL	CAS NUMBER	%	TLV
Chrysotile asbestos fiber - vulcanized in rubber	1332-21-4	65-85	0.5 f/cc
Elastomeric polymer	9003-55-8	12-25	
Pigments and curatives	-	5-10	

## II • PHYSICAL DATA

BOILING POINT N/A	SPECIFIC GRAVITY
SOLUBILITY IN WATER Nil	PERCENT VOLATILE
APPEARANCE AND ODOR Compressed rubber/asbestos sheet - slight rubber odor.	

## III • FIRE AND EXPLOSION DATA

FLASH POINT	FLAMMABLE LIMITS	LEL	UEL
EXTINGUISHING MEDIA CO <sub>2</sub> , dry chemical, water fog.			
SPECIAL FIREFIGHTING PROCEDURES Use self-contained breathing apparatus.			
UNUSUAL FIRE OR EXPLOSION HAZARDS			

## IV • HEALTH HAZARD INFORMATION

HAZARD BY ROUTES OF EXPOSURE (Indicate chronic or acute)	
INHALATION Asbestos is a known human carcinogen. Excessive exposure to high concentrations of dust can cause chronic pulmonary disease and cancer.	
INGESTION None	
EYE Transient irritant.	
SKIN CONTACT None	
SKIN ABSORPTION None	
SIGNS AND SYMPTOMS ASSOCIATED WITH EXPOSURE OVER TLV Upper respiratory irritation.	

HEALTH HAZARD INFORMATION CONTINUED ON BACK

**V • HEALTH HAZARD INFORMATION (Continued)****FIRST AID****INHALATION**

Remove to fresh air.

**INGESTION**

N/A

**EYE CONTACT**

Flush with copious quantities of water.

**SKIN CONTACT**

N/A

**SKIN ABSORPTION**

N/A

**VI • CONDITIONS FOR SAFE USE (When over TLV)****RESPIRATORY PROTECTION**

Use a respirator approved for protection against pneumoconiosis producing dusts.

**EYE PROTECTION**

Goggles are recommended during any mechanical cutting and punching operation.

**PROTECTIVE GLOVES**

Not normally required.

**OTHER PROTECTIVE CLOTHING/EQUIPMENT****VENTILATION REQUIREMENTS**

Local exhaust is recommended at mechanical cutting and punching operations.

**VII • REACTIVITY DATA****IS MATERIAL STABLE?**

Yes

**WILL HAZARDOUS POLYMERIZATION OCCUR?**

No

**INCOMPATIBILITY**

None

**CONDITIONS TO AVOID****HAZARDOUS DECOMPOSITION PRODUCTS**

None in designed use.

**VIII • SPILL OR LEAK PROCEDURES****STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR RELEASED**

Pick up large pieces, vacuum fine debris resulting from fabrication or installation.

**WASTE DISPOSAL METHOD**

Contains asbestos. Comply with local, state and federal regulations.

**LABELING REQUIRED?**

No, asbestos is encapsulated

**DOT REGULATED?****DOT NUMBER****RCRA REGULATED?****RCRA NUMBER****IX • SPECIAL PRECAUTIONS****SPECIAL PRECAUTIONS FOR HANDLING AND STORAGE****OTHER PRECAUTIONS****PREPARED BY**

Kenneth A. Roberts

**DATE**

7/15/83

**TITLE**

Mgr., Environmental Services

While the information and recommendations set forth herein are believed to be accurate as of the date hereof, THE MANUFACTURER MAKES NO WARRANTY WITH RESPECT THERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON.